




# dustnr

Bag filter for  
dust filtration

## DL 900 | DL 2000

Type	DL 900		DL 2000	
	N S	N T	N S	N T
Make				
Filter area [m <sup>2</sup> ]	4,5		10	
Suction performance [m <sup>3</sup> /h]	900 (800 Pa. ext.)		2.000 (800 Pa. ext.)	
Noise level [dB(A)]	~65		~73	
Weight [kg]	~90	~125	~185	~235
Power rating [kW]	0,75		2,2	
Voltage [V]	400/230			
Max. operating temp. [°C]	~40			
Height a [mm]	1.200	2.000	1.765	2.400
Length b [mm]	550		750	
Width c [mm]	650		850	

Subject to change without notice



**indusa GmbH**  
Daimlerstraße 8  
D-61267 Neu-Anspach

Tel.: +49 (0) 6081 95 870 - 0  
Fax: +49 (0) 6081 95 870 - 22  
www.indusa.de | info@indusa.de

**indusa**  
...pure air solutions



**duster**

	Bag filter	Cartridge filter	Automatic cleaning	Maximum airflow [m <sup>3</sup> /h]	Ext. pressure [Pa]	Differential pressure cleaning	Power rating [kW]	Dust drawer volume [l]	Dust barrel volume [l]	Polyester media	Blended fleece media	PTFE coated	B/A category C	Filter area	Spark-/ dust-pre-separator	Recommended pipe diameter [DN] mm
DL 900 N S	■	-	○	900	800	-	0,75-1,5	45	-	-	■	○	-	4,5 m <sup>3</sup>	○	120
DL 900 N T	■	-	○	900	800	-	0,75-1,5	-	60	-	■	○	-	4,5 m <sup>3</sup>	○	120
DL 2000 N S	■	-	○	2.000	800	-	2,2-3,0	45	-	-	■	○	-	10 m <sup>3</sup>	○	200
DL 2000 N T	■	-	○	2.000	800	-	2,2-3,0	-	90	-	■	○	-	10 m <sup>3</sup>	○	200
DL 1100 N S JET	-	■	■	1.100	700	■	1,1-1,5	45	-	■	○	○	■	10 m <sup>3</sup>	○	120
DL 1100 N T JET	-	■	■	1.100	700	■	1,1-1,5	-	60	■	○	○	■	10 m <sup>3</sup>	○	120
DL 2000 N JET	-	■	■	2.000	1.000	■	2,2-3,0	-	90	■	○	○	■	30 m <sup>3</sup>	○	200
DL 3000 N JET	-	■	■	3.000	1.000	■	3,0-4,4	-	180	■	○	○	■	60 m <sup>3</sup>	○	2 x 200
DL 2500 N JET	-	■	■	3.000	1.000	■	3,0	-	90	■	○	○	■	36 m <sup>3</sup>	○	250
DL 5000 N JET	-	■	■	6.000	1.000	■	4,4-6,0	-	180	■	○	○	■	72 m <sup>3</sup>	○	2 x 250

○ special equipment | ■ standard equipment | - not usable

Options	DL 900	DL 2000	DL 1100 JET	DL 2000 JET	DL 3000 JET	DL 2500 JET	DL 5000 JET
Special color				○			
Hand lever left or right	■				-		
Automatic cleaning	○				■		
Vacuum control system				○			
SPS/PLC management	○				■		
On-/off-line cleaning	- / ○				■ / ■		
Exhaust nozzle				○			
Cartridge monitoring	○				■		
400 V connector for IT-net				○			
Stronger ventilation [kW]				○			
Spark pre-separator				○			
EX-protection				○			
Potential free contact (error message) / on-off relay				○ / ○			
Wheel stand / extraction arm	○ / ○				- / -		
Safety after-filter H12 / active carbon after-filter (smell elimination)				○ / ○			

○ special equipment | ■ standard equipment | - not useable

Special construction on request

